

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
9 September 2005 (09.09.2005)

PCT

(10) International Publication Number
WO 2005/081844 A2

(51) International Patent Classification: Not classified

(21) International Application Number:
PCT/US2005/004958

(22) International Filing Date: 16 February 2005 (16.02.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/547,515 25 February 2004 (25.02.2004) US

(71) Applicant and

(72) Inventor: CRUTCHER, William, C. [US/US]; 84 Munson Road, Middlebury, CT 06762 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,

MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:


— of inventorship (Rule 4.17(iv)) for US only

Published:

— without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: CONVERTIBLE BARROW FOR GROUND LEVEL LOADING



(57) Abstract: Improvements to a known convertible barrow for ground level loading with a pivotable wheel carriage (36) for either resting on the ground for loading or pivoted under the barrow platform (20) for transporting a load. The improvements locate the pivot points (48) of the wheel carriage equidistant from the wheel carriage when it is adjacent the inclined rear wall (18), when it passes the heel end (24) during pivoting and when it is adjacent the midpoint of the platform to obtain a minimum, tilt angle during conversion. A pivotable gate (36) provides a closure member (56) for retaining the load at the time of tilting the barrow and is pivotable about pivot points (55) on arms (58, 60) to an open position.



WO 2005/081844 A2